

# ATTESTATION OF CONFORMITY

Issued to: SHENZHEN MOSO ELECTRONICS TECHNOLOGY CO., LTD  
No. 1061, Songbai Road, Xili, Nanshan District, 518108 Shenzhen City, Guangdong Province, China

For the product: Independent LED drivers

Trade name: MOSO

Type/Model: XCP-042M062-F, LCP-042M062-F, XCP-042M062, LCP-042M062, XCP-060M062-F, LCP-060M062-F, XCP-060M062, LCP-060M062

Ratings: see annex

Manufactured by: SHENZHEN MOSO ELECTRONICS TECHNOLOGY CO., LTD  
No. 1061, Songbai Road, Xili, Nanshan District, 518108 Shenzhen City, Guangdong Province, China

Requirements: EN 61347-1:2015 + A1:2021  
EN 61347-2-13:2014 + A1:2017  
EN 62493:2015 + A1:2022

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 4911552.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 14 December 2023

Number: 4911552.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,  
Guangzhou Branch



May Liu  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed



# Annex

---

Document no. : 4911552.01AOC

Ratings:

Independent, non-inherently short-circuit proof, tc 90 °C, IP67, class II, SELV, constant current type, 110 °C thermal protection

XCP-042M062, LCP-042M062, LCP-042M062-F, XCP-042M062-F:

Input: AC 100-277 V, 50/60 Hz, max. 0,7 A, max. 55 W, ta 55 °C,

PF: 0,9C-0,97 (Pout ≥ 35 W);

Output: 0,105-1,05 A, 35-62 Vdc, Uout 80 Vdc, Max. 42 W;

XCP-060M062, LCP-060M062, XCP-060M062-F, LCP-060M062-F:

Input: 50/60 Hz, max. 0,85 A, max. 76 W, PF: 0,9C-0,97 (Pout ≥ 50 W),

AC 100-200 V: ta 50 °C,

AC 200-277 V: ta 55 °C;

Output: 0,13-1,3 A, 32-62 Vdc, Uout 85 Vdc, Max. 60 W

---

End