

Specification for Approval

Product Name: 350W Constant Voltage LED Driver

Product Model: V6E-350B036

Rev. A.2

CUSTOMER AUTHORIZED SIGNATURE		
Tested By	Checked By	Approved By
(Company seal)Return one copy to MOSO with approved signature and company seal.		

XiLi Songbai Road 1061, Nanshan	
Address: District, Shenzhen City, Guangdong	Post Code: 518108
Province, P.R.China	
TEL: 0755-27657000	FAX: 0755-27657908
E-mail: info@mosopower.com	Web site: http://www.mosopower.com

Prepared By	Checked By	Approved By

Product Specification

Product Name: 350W Constant Voltage LED Driver

Product Model: V6E-350B036

Rev. A.2

Address: XiLi Songbai Road 1061, Nanshan District, Shenzhen City, Guangdong Province, P.R.China

Post Code: 518108

TEL: 0755-27657000

FAX: 0755-27657908

E-mail: info@mosopower.com

Web site: <http://www.mosopower.com>

Prepared By	Checked By	Approved By

REVISION HISTORY

[illegible]



Product Features:

- ◆ Input voltage: 176~264Vac;
- ◆ Constant voltage output;
- ◆ High power factor >0.97(230Vac& full load);
- ◆ THD<10%;
- ◆ Protection: Input UVP, output SCP, OVP, OTP, OCP;
- ◆ Surge immunity: DM6KV, CM10KV;
- ◆ IP67, glue potted, suitable for dry / wet / damp locations;
- ◆ 5 years warranty.

Application

- ◆ Suitable for landscape lighting.

DESCRIPTION

The V6E-350 series is a 350W constant-voltage, the LED driver that operates from 176~264Vac input with excellent power factor and low THD. It is designed for landscape lighting. The high efficiency of the driver and compact metal case enables them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, under voltage, output over current, over voltage, short circuit, and over temperature.

MODELS

Model Number	Max Output Power(W)	Output Voltage (Vdc)	Output Current Range (A)	Typical Efficiency	Typical PF	Typical THD
V6E-350B036	350	36	0~9.80	93%	0.98	10%

Notes:

1. All performance parameters are measured at 25°C ambient temperature, 230Vac input, full load conditions, except for those specified;
2. The drivers are not allowed to work in over-load condition, otherwise warranty will expire.

INPUT SPECIFICATIONS

Parameter	Min.		Typ.		Max.		Notes
Input Voltage	176Vac		200-240Vac		264Vac		
Input Frequency	47Hz		50/60		63Hz		
Leakage Current	-		-		0.70mA		240Vac/60Hz
Input AC Current	-		-		2.5A		200-240Vac & full load
Inrush Current	-		-		5.5 A²S		Cold start, 10%Ipeak, 230Vac & full load
Power Factor	0.96		0.98		-		220-240Vac , 50-60Hz&full load
	0.95		0.97		-		220-240Vac , 50-60Hz& 75% load
	0.90		0.93		-		220-240Vac , 50-60Hz& 50% load
THD	-		10%		15%		220-240Vac,50-60Hz, 80%~100% load
	-		15%		20%		220-240Vac,50-60Hz, 50%~80% load
Max. No. of PSUs on CIRCUIT BREAKER	B10	1	B16	1	B25	2	230Vac
	C10	1	C16	2	C25	4	

OUTPUT SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Notes
Output Voltage Tolerance	-2%	-	+2%	Full load
Total Output Voltage Ripple(pk-pk)	-2%		+2%	Full load, Measured by 20 MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 47uF electrolytic capacitor.
Output overshoot	-5%	-	+5%	When the power is on
Line Regulation	-0.5%	-	+0.5%	25°C±10°C ambient temperature, input voltage changes from 176Vac to 264Vac.
Load Regulation	-2%	-	+2%	25°C±10°C ambient temperature, 230Vac input, load changes from 0% to 100%.
Turn-on Delay Time	-	-	0.5S	230Vac, 100% load

GENERAL SPECIFICATIONS

Parameter		Min.	Typ.	Max.	Notes
Efficiency@230Vac		92%	93.5%	-	40%~100% load
Dielectric Strength	Input-Output	-	3750Vac		5mA/60S
	Input-PE	-	1875Vac		
	Output-PE	-	500Vac		
Grounding Resistance		-	-	0.1Ω	25A/60S
Insulation Resistance		10MΩ	-	-	Input-Output, Input-PE, Output-PE, 500Vdc/60S/ 25℃/70%RH
MTBF			1232.28K hrs		Telcordia SR-332 (Bellcore)
		-	200Khrs	-	230Vac, (MIL-HDBK-217F)
Lifetime		-	50000Hours	-	230Vac&100% load, 75℃ case temperature, refer to lifetime VS Tc curve for details
Ambient Temperature		-40℃		+55℃	
Operating Case Temperature for Safety Tc_s		-40℃	-	+90℃	
Operating Case Temperature for Warranty Tc_w		-40℃	-	+75℃	5 years warranty case temperature Humidity: 10% to 100% RH
Storage Temperature		-40℃	-	+90℃	Humidity: 10% to 100% RH
Dimensions (L*W*H)mm		L224.5*W96.9*H41.8			
Net Weight		1700±100g/PCS			
Package		L610*W370*H160mm; 10PCS/Ctn.; Gross Weight: 18.8kg			

SAFTY STANDARDS

Safety Category	Country / Territory	Standards	Approved
CCC	China	GB19510.1, GB19510.14	√
CE	Europe	EN61347-1, EN61347-2-13	√
		EN62493	√
ENEC		EN62384	
CB	CB Countries	IEC61347-1, IEC61347-2-13	
BIS	India	IS 15885(PART 2/SEC 13)	
UL	USA	UL 8750	
CUL	Canada	CSA C22.2 No.250.13	
KC	South Korea	K61347-1, K61347-2-13	
PSE	Japan	J61347-1, J61347-2-13	
SAA	Australia	AS/NZS IEC 61347.2.13	
		AS/NZS 61347.1	


EMC COMPLIANCE

EMC Category	Country / Territory	Standards	Approved
CCC	China	GB/T 17743, GB 17625.1	√
CE	Europe	EN 55015	√
		EN 61000-3-2, EN 61000-3-3	√
		EN61000-4-2,3,4,5,6,11	√
		EN 61547	√
KC	South Korea	K61547	
		K00015	
PSE	Japan	J55015	
FCC	USA	FCC part 15	


NOTE:

This LED driver meets the EMI specifications above, but as a component of a luminaire, end customer need to identify the EMI performance of a luminaire including LED driver, other devices connected to the driver and on the luminaire itself.


INRUSH CURRENT WAVEFORM




DERATING CURVE




OUTPUT POWER VS INPUT VOLTAGE CURVE




LIFETIME VS CASE TEMPERATURE




EFFICIENCY VS LOAD



POWER FACTOR VS LOAD




TOTAL HARMONIC DISTORTION



PROTECTIONS


Parameter	Min.	Typ.	Max.	Notes
Input under voltage protection	156Vac /50Hz	-	176Vac /50Hz	Turn off the output or hiccup when the input voltage falls below protection voltage.
Over temperature protection	Output drop current. Returning to normal after over temperature is removed.			
Short circuit protection	Hiccup mode. The output shall return to normal when the fault condition is removed.			
Over current protection	Hiccup mode. The output shall return to normal when the fault condition is removed.			
Over voltage protection	Turn off the output voltage, when the fault is removed, restart and resume.			

MECHANICAL OUTLINE



Wire	Specification	Note
Input	CCC+VDE 3*1.0mm ² OD: 7.15mm L=300±20mm	CCC/CE
Output	CCC+VDE 2X1.5 mm ² OD: 9.6mm L=300±20mm	CCC/CE

LABEL



ROHS

Our products comply with reference to RoHS Directive (EU) 2015/863 amending 2011/65/EU.